

Allstates Coatings Co.® PRODUCT INFORMATION

P.O. Box 1633 ● 100 Lee Street ● Gladewater, TX 75647
903-845-6436 ● 1-800-358-3020 ● Fax: 903-845-5626

ALT - 300 Clear Kote

www.allstatescoatings.com

MANUFACTURERS OF PAINT & COATINGS

ALT - 300 Clear Kote

GENERAL: A quick drying modified barrier coating, formulated to coat and protect concrete, metal, wood, and asphaltic surfaces from oxidization effects. Clear Kote is a clear, water-based acrylic system that can be easily used as a non-hazardous water-soluble water repellent and rust preventative that is chemical and solvent resistant.

SURFACE

PREPARATION: Surface areas to be treated must be free from dirt and dust. Scrape excessive build-up of oil, grease or any other chemical stain spots. Lightly burn off excessive oil build up.

APPLICATION: Mix well before using. Normal use is full strength. Reduce 1 to 1 or 1 to 2 with water, depending on the porosity of the substrate and desired viscosity. Can be applied with a suitable spray machine, pushbroom, brush or roller.

COVERAGE: 300-400 ft.² per dilute gallon.

CAUTION: **KEEP FROM FREEZING.** Wash tools in water. Use suitable paint thinner if material has dried. Do not store in direct sunlight. Container should be closed when not in use. Keep out of the reach of children.

PACKAGING: 5 gallon pails, 55 gallon drums and 275 gallon tote tanks.

Material Specifications:

Requirements:

Weight per Gallon, ASTM D1010, (lbs)	8.70 - 8.90
Viscosity @ 77°F ASTM D562 (Kreb's Stormer Unit).....	70 - 85 KU
% Nonvolatile by weight	48 - 50
Drying Time (min)	45 - 60
Application Temp (°F).....	45 min.
Film forming tester over oil	Film must form over oily surfaces
Flammability	non-flammable
VOC Requirements.....	0.55 lbs/gal