

Allstates Coatings Co.™ PRODUCT INFORMATION

P.O. Box 1633 ● 100 Lee Street ● Gladewater, TX 75647
903-845-6436 ● 1-800-358-3020 ● Fax: 903-845-5626

*ALT-625 Poly Allstates White
Tennis Court Line Paint*

MANUFACTURERS OF PAINT & COATINGS

ALT-625 Poly Allstates White Tennis Court Line Paint

GENERAL: For exterior use on asphalt surfaces. An acrylic latex emulsion of superior quality that is exceptionally tough, durable, and attractive. It is ready to use on tennis courts, running tracks, play areas and parking lots.

SURFACE

PREPARATION: Surface must be free from dirt and oil. Do not stripe when rain is forecast, when surface is wet, or when temperature is below 50°F. Contact Allstates for detailed applications.

APPLICATION: Mix well before using. If applied by spray, strain and dilute slightly with water if needed. For brush or roller use as is. Dries in less than thirty minutes. In shaded areas or cooler temperatures longer drying time may be required. Under normal drying conditions no traffic pick-up after 4 to 6 hours.

COVERAGE: 900 linear of 2" stripe per gallon (Need less than 1 gallon paint per tennis court)

CAUTION: **KEEP FROM FREEZING.** Wash tools in water. Use a suitable paint thinner if material has dried. Do not store in direct sunlight. Container should be closed when not in use. Because alkali inherent in concrete surfaces there is no product guarantee on these. Keep out of the reach of children. For exterior use only.

PACKAGING: 1 gallon cans, 5 gallon pails, and 55 gallon drums

Material Specifications:

Requirements:

Weight per Gallon, ASTM D1010 (lbs)	10.60 - 10.90
Viscosity @ 77°F ASTM D562 (Kreb's Stomer Unit).....	85 - 95 KU
% Solids by Weight.....	48.00 ± 2.00
Scrub Resistance, cycles ASTM D248	400
Freeze, than stability ASTM D2243	5 cycles
Volatile Organic Content (lbs/gal.)	0.25
Flammability.....	non flammable

Notes on Striping a Tennis Court

- * Hand application requires masking tape for definition; masking tape applicators are available for taping.
- * To provide clean, sharp lines, paint area to be striped with clear acrylic coat first, allow the stripe to dry and proceed to stripe with color.
- * Add 2lbs of silica sand (80-100 mesh) / 1 gallon of White Tennis Court line paint to achieve a textured line that matches playing surface.