

Allstates Coatings Co.® PRODUCT INFORMATION

P.O. Box 1633 ● 100 Lee Street ● Gladewater, TX 75647
903-845-6436 ● 1-800-358-3020 ● Fax: 903-845-5626
www.allstatescoatings.com
MANUFACTURERS OF PAINT & COATINGS

*ALT-672 Lightning Graphic®
Field Marking Concentrate Paint*

ALT-672 Lightning Graphic® **Field Marking Concentrate Paint**

Available colors: White, Yellow, Blue, Red, Black and Green

GENERAL: **Air Brush Color System** formulated with acrylic polymer emulsions of superior quality that is exceptionally tough, durable and attractive. It is water based and does not contain any mercury or lead pigments. Complies with all V.O.C. emissions and is not a hazardous substance under current OSHA definitions. Use on any athletic field like football, baseball, soccer and track & field (natural and artificial turf or asphalt and concrete surfaces). Good for educational graphics and logos.

SURFACE

PREPARATION: Surface must be clean - free from dirt and oil. Do not apply while rain is in forecast, on wet surface, or when temperature is below 45°F.

APPLICATION: Mix well before using. For first application, use as is. Additional applications dilute with water as desired. Drying time is approximately 30 – 60 minutes. Longer drying time may be required with lower temperatures and higher humidity. Touch-up applications may be further diluted. Concentrate should be mixed, in base form, thoroughly before adding water then mixed again after water is added, to achieve proper mix. Always strain paint before loading into machine. Fields should be painted within 48 hours of event for best results, weather permitting. When painting new lines or colors, two applications should be planned.

COVERAGE: Up to 500 Linear feet of 4" stripe per gallon undiluted
300 to 400 square feet per gallon undiluted @ 6.8 mil. wet

CAUTION: **KEEP FROM FREEZING.** Wash tools in water. Use a suitable paint thinner if material has dried. Do not store in direct sunlight. Container should be closed when not in use. Keep from freezing. Keep out of the reach of children. **FOR EXTERIOR USE ONLY:** This product is intended solely for exterior use in well ventilated areas.

PACKAGING: 5 gallon pails

IMPORTANT: Custom colors are available - minimum of 50 gallons

Material Specifications:

Requirements:

Weight per Gallon, @ 77°F, ASTM D1010, (lbs)	12.30 – 12.80
Viscosity @ 77°F ASTM D 562 (Kreb's Stormer Unit)	115 - 125 KU
% Nonvolatile by weight + or – 2.00 (ALT-685).....	55.00
Grind fines Hegman	2 - 3
Application Temp (°F)	45 min.
Flammability	non flammable
VOC Requirements	less than 0.50 lbs/gal