

# Allstates Coatings Co.® PRODUCT INFORMATION

P.O. Box 1633 ● 100 Lee Street ● Gladewater, TX 75647  
903-845-6436 ● 1-800-358-3020 ● Fax: 903-845-5626  
www.allstatescoatings.com  
MANUFACTURERS OF PAINT & COATINGS

*ALT-692 E-Z Off™  
Field Marking Paint*

## ***ALT-692 E-Z Off™ Field Marking Paint*** Environmental Advantages of a Aqueous System Available Colors: Black

**GENERAL:** ALT-692 E-Z Off Field Marking Color System is formulated with acrylic polymer emulsions of superior quality that is attractive and easy to remove. It is aqueous based and does not contain any mercury or lead pigments. This product complies with all V.O.C. emissions and is not a hazardous substance under current OSHA definitions. It is ready to use on athletic areas, educational graphics, logos, natural or artificial turf and any asphaltic or concrete surfaces (streets, parking lots, etc...)

**SURFACE PREPARATION:** Surface must be clean, free from dirt and oil. Do not apply when rain is in forecast, on wet surface, or when temperature is below 45°F.

**APPLICATION:** Mix well before using. Additional applications dilute with water as desired. Field marking paints come in a concentrated form and are intended to be diluted with water. Thoroughly stir before and after dilution for proper mix. Always strain before loading into any machine. Drying time is less than 30 minutes; however, extra time should be allowed under lower temperatures and higher humidity. Drying may be accelerated by applying heat or air. Fields should be painted within 48 hours of event for best results, weather permitting. When painting new lines or colors, two applications should be planned.

**COVERAGE:** Up to 500 linear feet of 4" stripe per gallon undiluted  
100 to 125 square feet per gallon undiluted

**CAUTION:** Wash tools in water. Use a suitable paint thinner if material has dried. Keep from freezing. Do not store in direct sunlight. Container should be closed when not in use. Because of alkali inherent in concrete surfaces, there is no product guarantee on these, keep out of the reach of children.  
**FOR EXTERIOR USE ONLY.** This product is intended solely for exterior use in well ventilated areas. Use of this product inside or to treat any materials used inside any building or structure, may be hazardous to the health of those occupying the building.

**PACKAGING:** Five gallon pails.

Material Specifications:	Requirements:
Weight per Gallon, @ 77°F, ASTM D1010, (lbs) .....	10.8 - 11.20
Nonvolatile %, ASTM D2939 .....	41.00 - 45.00
Viscosity @ 77°F (Krebs Stormer Unit) .....	95 - 110
Flammability .....	Non-flammable
PH .....	5.00-6.00

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to the suitability of the contents. Nothing herein shall constitute a warranty, express or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent implied. 12/8/05