

Allstates Coatings Co.® PRODUCT INFORMATION

100 N. Lee Drive ● Gladewater, TX 75647
903-845-6436 ● 1-800-358-3020 ● Fax: 903-845-5626
www.allstatescoatings.com
MANUFACTURERS OF PAINT & COATINGS

ALT - 300 Clear Kote

ALT - 300 Clear Kote

GENERAL: A quick drying modified barrier coating, formulated to coat and protect metal, concrete, wood, and asphaltic surfaces from oxidization effects. Clear Kote is a clear, water-based acrylic system that can be easily used as a non-hazardous water-soluble water repellent and rust preventative that is chemical and solvent resistant.

SURFACE

PREPARATION: Surface areas to be treated must be free from dirt and dust. Scrape excessive build-up of oil, grease or any other chemical stain spots. Lightly burn off excessive oil build up.

APPLICATION: Mix well before using. Normal use is full strength and is for a dip application.

COVERAGE: 150 - 200 ft.² per gallon.

CAUTION: **KEEP FROM FREEZING.** Wash tools in water. Use suitable paint thinner if material has dried. Do not store in direct sunlight. Container should be closed when not in use. Keep out of the reach of children.

PACKAGING: 5 gallon pails, 55 gallon drums, 275 gallon tote tanks and bulk.

Material Specifications:

Requirements:

Weight per Gallon, ASTM D1010, (lbs)	8.50 - 8.60
Viscosity @ 77°F ASTM D562 (Kreb's Stormer Unit).....	50 KU
% Nonvolatile by weight	30 - 32
Drying Time (min)	15
Application Temp (°F).....	45 min.
Flammability	non-flammable
VOC Requirements.....	0.45 lbs/gal
Reducer Type.....	water