

Allstates Coatings Co.[®] PRODUCT INFORMATION

100 N. Lee Drive • Gladewater, TX 75647
903-845-6436 • 1-800-358-3020 • Fax: 903-845-5626
www.allstatescoatings.com
MANUFACTURERS OF PAINT & COATINGS

ALT-648
CT-200-Chemical Thickener

CT-200 Chemical Thickener

General: Chemical Thickener is a chemically swellable polymeric emulsion which exhibits viscosity build-up for pourable crack filler, asphalt and coal tar emulsion type sealer. Viscosity is developed by neutralization to a pH of 7 to 10 of the finished products such as crack filler, asphalt and coal tar sealer.

This is a chemical viscosity builder for coal tar sealer and pourable crack filler. It is post additive and can be added at the end of the batch to increase viscosity and clay / sand suspension. We recommend to add 1 pint to 1 quart (premix with equal amount of water before adding to the batch) of CT-200 per 100 gallons of either coal tar sealer or crack filler under proper agitation. Always add slowly and mix thoroughly for 5 minutes to react. However, the amount of CT-200 will vary depending upon the pH of the finished product.

Material Specifications:

Results:

| | |
|-------------------------------|-------------------------------|
| General Type | Compounded Polymeric Emulsion |
| Appearance | Grayish Blue |
| Specific Gravity @ 77°F | 1.0-1.05 |
| % Non Volatile Material | 15.00-17.00 |
| Viscosity @ 77°F (KU)..... | 45.00-50.00 |
| Odor..... | Mild |
| Storage Requirements..... | Protect from freezing |
| Flash Point..... | None |
| Flammability | Non Flammable |
| pH | 3.50-4.50 |